



Modern Automotive Technology Chapter 72


Brake System Diagnosis And Repair



North Montco
Technical Career Center

Learning Objectives

- Diagnose common brake system problems.
- Inspect and maintain a brake system.
- Describe basic procedures for servicing a master cylinder and a brake booster.
- Explain how to service a disc brake assembly.
- Explain how to service a drum brake assembly.
- Describe the procedures for both manual and pressure bleeding of a brake system.
- Cite the safety rules that should be followed when servicing brake systems.




Chapter 72


1. Brake Pedal Free-Play is needed to prevent brake drag and overheating.
2. Excessive Brake Pedal Effort is a noticeable increase in the amount of pressure needed to apply brakes and stop vehicle.



Brake System Problems



Brake Pedal Free-Play



Excessive Pedal Effort

- Noticeable increase in the amount of foot pressure needed to apply the brakes
- Possible causes:
 - seized wheel cylinder or caliper piston
 - collapsed brake hose or crimped line
 - faulty master cylinder
 - contaminated linings
 - disconnected brake booster vacuum line or defective booster



Chapter 72

3. Dropping Brake Pedal (Fading) is a symptom where brake pedal slowly moves all the way to the floor when steady pressure is applied to it.
4. Brake Shoe Lining must not be worn thinner than about $1/16''$ ($2/32''$, 1.5 mm).




Dropping Brake Pedal

- Pedal slowly moves all the way to the floor when steady pressure is applied to it
- Pumping usually restores pedal height momentarily
- Possible causes:
 - internal leak in the master cylinder
 - external fluid leak in any component



Disc Brake Inspection



Inspect brake pad linings for thickness, must not be less than $1/16''$ ($2/32''$, 1.5 mm).



Chapter 72

5. A Spongy Brake Pedal is a condition in which brakes apply but pedal does not feel solid; it will travel farther to the floor before full braking action occurs.
6. Grabbing is a condition in which brakes apply too quickly, with only light brake pedal application.



Spongy Brake Pedal

- Brakes will apply, but the pedal does not feel solid
- Possible causes:
 - air in the brake system
 - faulty residual check valve in the master cylinder
 - maladjusted brake shoes




Grabbing Brakes

- Brakes apply too quickly, even with light brake pedal application
- Possible causes:
 - malfunctioning brake booster
 - brake fluid or grease on the linings
 - worn brake linings
 - faulty metering valve
 - mechanical problem in the wheel brake assembly



Causes of Grabbing



Check the drum for cracks or heat damage

A badly scored drum must be machined

Check for weak springs & leaking wheel cylinders




Chapter 72

7. Brake Pedal Height is the distance from pedal to floor with the pedal at rest.
8. Pulling Brakes causes a vehicle to veer right or left when braking.



Brake Pedal Height



Pulling Brakes

- Vehicle veers to the right or left when the brakes are applied
- Possible causes:
 - seized caliper or wheel cylinder piston
 - grease or fluid-coated lining
 - leaking cylinder
 - faulty automatic adjuster
 - brake lining dust in a drum brake assembly




Chapter 72


9. Brake Fluid Level should be 1/4" from top of reservoir.
10. Brake Pedal Vibration is usually caused by an out-of-round brake drum or warped disc.



Checking Brake Fluid




Disc Brake Inspection




Inspect rotors: scoring, cracks, out-of-round, and/or heat damage can cause brake pedal vibration



Disc Brake Inspection




Bleeding Brakes



Bleeding brakes removes air from the brake system




Pressure Bleeding



Uses a pressure bleeder tank, which contains brake fluid under pressure




Double Flaring a Brake Line




On-Car Brake Lathe


Lathe assembly has controls for feeding cutters into the disc surface



Disc Brake Reassembly



Measuring Brake Drum Diameter




Typically, a drum should not be machined more than 0.060" (1.5 mm) oversize

Drum diameter is often stamped on the drum

Use a drum micrometer to measure the diameter



Parking Brake Cables



Learning Objectives

- Diagnose common brake system problems.
- Inspect and maintain a brake system.
- Describe basic procedures for servicing a master cylinder and a brake booster.
- Explain how to service a disc brake assembly.
- Explain how to service a drum brake assembly.
- Describe the procedures for both manual and pressure bleeding of a brake system.
- Cite the safety rules that should be followed when servicing brake systems.

